DECLARATION OF PERFORMANCE No.

Year of issue

07

4086



effect glass S.A. ul. Hauke Bosaka 2 25-214 Kielce Poland effect glass S.A. Wędkowy Branch 83-115 Swarożyn Poland

according to requirements of the standard:

PN-EN 1279-5+A2:2011 Schedule ZA

name / intended use of the product:

insulated glass unit / for use in construction industry and construction works

identification of the product:

4LE/10/4/10/44.2LE+A

Characteristics:		Value:	Standard
Fire resistance		NPD	EN-13501-2
Reaction to fire		NPD	EN-13501-1
Behavior of external fire		NPD	
Bullet resistance		NPD	EN 1063
Explosion resistance		NPD	EN 13541
Resistance against manual attack		NPD/NPD/P2A	EN 356
Pendulum body impact resistance		NPD/NPD/1B1	EN 12600
Resistance against sudden temperature changes and temperature differentials	[°K]	40/40/40	EN 572
Wind, snow, permanent and imposed load resistance	[mm]	4/4/6	
Airborne sound insulation	$R_w(C;C_{tr})$ [dB]	NPD	EN 12758
Light transmittance factor	$\tau_{\sf v}[\%]$	73	EN 410
Light reflectance factor	$\rho_{v} / \rho'_{v} [\%]$	14/14	EN 410
Solar direct transmittance factor	$ au_{ m e}$ [%]	44	EN 410
Solar direct reflectance factor	$\rho_e/\rho'_e[\%]$	32/24	EN 410
Total solar energy trasmittance factor	g [%]	54	EN 410
Termal trasmittance factor	U [W/m²K]	0,8	EN 673
NPD - No performance determined			

Effect Glass S.A. declares, under its sole responsibility, that the construction product is in conformity with the above performance characteristics.

Technical Director

Kielce. 2016-11-18

Waldemar Bratek

Notified Body taking part in conformity assessment of the product:

Institute of Ceramics and Building Materials in Warsaw. Glass and Building Materials Division in Cracow. Glass Technology Unit. 30-702 Cracow ul. Lipcowa 3 - Initial Type Testing

Institute of Ceramics and Building Materials in Warsaw. Ceramics and Glass Section. 02-676 Warsaw ul. Postępu 9 - Factory Production Control Certificate, Conformity Certificate acc. To. PN-EN 1279-5

Schedule no. 1 to the Declaration of Performance:

Copy of particulars accompanying CE marking